





Socket Connectors 2.54mm : SBD

Single Row/Double Row Straight Solder Tail



SPECIFICATIONS:

Insulator:	PPS
Flammability:	UL 94V-0
Sleeve:	Brass
Contact clip (4 finger):	Beryllium copper
Mating pin ϕ :	0.40 to 0.56 mm
Forces:	(polished steel gauge ϕ 0.43mm)
-Insertion	3 N typ.
-Withdrawal	1.5 N typ.
Mechanical life:	min 500 cycles
Rated current:	3 A
Contact resistance:	max 10 m Ω
Dielectric strength:	min 1000V RMS






P.C.B LAYOUT

SBDXX011XX0482A

Straight socket connector ultralow profile height 2.4mm: solder tail, single row

Availability from: 2 to 40 contacts
32, Standard number of contacts 20 and 40






P.C.B LAYOUT

SBDXX212XX0482A

Straight socket connector ultralow profile height 2.4mm: solder tail, double row

Availability from: 4 to 80 contacts
56, Standard number of contacts 20 and 72






P.C.B LAYOUT

SBDXX041XX540A

Straight socket connector height 3.0mm: solder tail, single row

Availability from: 1 to 40 contacts
Standard number of contacts 5, 6, 8, 9, 10, 11, 12, 14, 16, 17, 20, 25, 30, 32 and 40



P.C.B LAYOUT

SBDXX242XX0540A

Straight socket connector height 3.0mm: solder tail, double row

Availability from: 2 to 80 contacts
Standard number of contacts 20, 56, 60 and 72

XX	X	XX	X	X	X	X	X	XXXXX
Pitch(mm) SA 2.54 Male SB 2.54 Female SC 2.00 Male SD 2.00 Female SE 1.778 Male SF 1.778 Female SG 1.27 Male SH 1.27 Female	Angel Options D Straight R Right Angle S SMT	No. of Positions XX Positions	Dip spacing 0 No 1 1.27mm 2 2.54mm 3 7.62mm 4 10.16mm 6 15.24mm 9 22.86mm S Special	Insulator Height 0 No 1 1.90 mm 2 2.00 mm 3 2.80 mm 4 3.00 mm 5 4.20 mm 6 7.00 mm S Special	Insulator Type 0 No 1 Single Row 2 Double Row 3 Open frame 4 W/O Bar S Special	Pin Plated 0 No 1 Tin150 μ " 2 Tin200 μ " 3 G/F 4 Gold3 μ " 5 Gold10 μ " 6 Gold15 μ " S Special	Clip Plated 0 No 1 Tin150 μ " 2 Tin200 μ " 3 G/F 4 Gold3 μ " 5 Gold10 μ " 6 Gold15 μ " S Special	Pin length Options 0482A 4.82mm 0540A 5.40mm S Special