





Pitch 1.27mm Female Header : F113,F114,F136

Pitch 1.27mm Female Header,SMT Single Row
06 to 50Positions







SPECIFICATIONS:
Current Rating : 1AMP
Operation Temperature : -40°C to +105°C
Contact Resistance : 20mΩ Max
Insulation Resistance : 1000MΩ Min
Withstanding Voltage : AC500V
Insulator Material : Polyester (UL94V-0)
Standard: Nylon-6T
Contact Material : Phosphor Bronze
Contact Plating : Au or Sn over 50u"Ni




TYPE A
TYPE B
P.C.B LAYOUT

Pitch 1.27mm Female Header,SMT Dual Row
06 to 100Positions



SPECIFICATIONS:
Current Rating : 1AMP
Operation Temperature : -40°C to +105°C
Contact Resistance : 20mΩ Max
Insulation Resistance : 1000MΩ Min
Withstanding Voltage : AC500V
Insulator Material : Polyester (UL94V-0)
Standard: Nylon-6T
Contact Material : Phosphor Bronze
Contact Plating : Au or Sn over 50u"Ni






P.C.B LAYOUT


F113	11	XX	XX	S	X	A
Insulator Height F113 H=2.10	Insulator Type 11 Single Row	No. of Positions 06 ~ 50 Positions	Pin Plating SN Tin G0 Gold Flash G2 Gold2u" * G3 Gold5u" * G4 Gold10u" * G5 Gold15u" * G6 Gold30u" * S0 Gold Flash/Tin Standard : G0	Angle Options S SMT	Insulator C Nylon-6T D LCP E Nylon-46	Series No. A OE=3.10mm

F113	12	XX	XX	S	X	A
Insulator Height F113 H=2.10	Insulator Type 12 Double Row	No. of Positions 06 ~ 100 Positions	Pin Plating SN Tin G0 Gold Flash G2 Gold2u" * G3 Gold5u" * G4 Gold10u" * G5 Gold15u" * G6 Gold30u" * S0 Gold Flash/Tin Standard : G0	Angle Options S SMT	Insulator C Nylon-6T D LCP E Nylon-46	Series No. A OE=4.40mm

Pitch 1.27mm Female Header,Straight
Single Row & Double Row 06 to 100Positions







SPECIFICATIONS:
Current Rating : 1AMP
Operation Temperature : -40°C to +105°C
Contact Resistance : 20mΩ Max
Insulation Resistance : 1000MΩ Min
Withstanding Voltage : AC500V
Insulator Material : Polyester (UL94V-0)
Standard: Nylon-6T
Contact Material : Phosphor Bronze
Contact Plating : Au or Sn over 50u"Ni




P.C.B LAYOUT

Pitch 1.27mm Female Header,SMT Single Row
06 to 50Positions



SPECIFICATIONS:
Current Rating : 1AMP
Operation Temperature : -40°C to +105°C
Contact Resistance : 20mΩ Max
Insulation Resistance : 1000MΩ Min
Withstanding Voltage : AC500V
Insulator Material : Polyester (UL94V-0)
Standard: Nylon-6T
Contact Material : Phosphor Bronze
Contact Plating : Au or Sn over 50u"Ni



TYPE A
TYPE B
P.C.B LAYOUT

FXXX	XX	XX	XX	D	X	A
Insulator Height F113 H=2.10 F114 H=3.40 F136 H=4.40	Insulator Type 11 Single Row 12 Double Row	No. of Positions 06 ~ 100 Positions	Pin Plating SN Tin G0 Gold Flash G2 Gold2u" * G3 Gold5u" * G4 Gold10u" * G5 Gold15u" * G6 Gold30u" * S0 Gold Flash/Tin Standard : G0	Angle Options D Straight	Insulator C Nylon-6T D LCP E Nylon-46	Series No. A OE=2.40mm

FXXX	11	XX	XX	S	X	B
Insulator Height F114 H=3.40 F136 H=4.40	Insulator Type 11 Single Row	No. of Positions 06 ~ 50 Positions	Pin Plating SN Tin G0 Gold Flash G2 Gold2u" * G3 Gold5u" * G4 Gold10u" * G5 Gold15u" * G6 Gold30u" * S0 Gold Flash/Tin Standard : G0	Angle Options S SMT	Insulator C Nylon-6T D LCP E Nylon-46	Series No. B OE=3.40mm