





Pitch 2.0mm Female Header : F121,F122,F137,F138

Pitch 2.0mm Female Header,SMT Dual Row
02 to 80 Positions






SPECIFICATIONS:
Current Rating : 1.5AMP
Operation Temperature : -40°C to +105°C
Contact Resistance : 20mΩMax
Insulation Resistance : 1000MΩMin
Withstanding Voltage : AC 500V
Insulator Material : Polyester (UL94V-0)
Standard: LCP
Contact Material : Phosphor Bronze
Contact Plating : Au over 50u"Ni




P.C.B LAYOUT

Pitch 2.0mm Female Header,SMT Dual Row
02 to 80 Positions



SPECIFICATIONS:
Current Rating : 1.5AMP
Operation Temperature : -40°C to +105°C
Contact Resistance : 20mΩMax
Insulation Resistance : 1000MΩMin
Withstanding Voltage : AC 500V
Insulator Material : Polyester (UL94V-0)
Standard: Nylon-66
Contact Material : Phosphor Bronze
Contact Plating : Au over 50u"Ni






P.C.B LAYOUT


F121	12	XX	XX	S	X	A
Insulator Height F121 H=2.10	Insulator Type 12 Double Row	No. of Positions 02~80 Positions	Pin Plating SN Tin G0 Gold Flash G2 Gold25μ" G3 Gold5μ" G4 Gold10μ" G5 Gold15μ" G6 Gold30μ" S0 Gold Flash/Tin Standard: G0	Angle Options S SMT	Insulator C Nylon-6T D LCP	Series No. A OE=5.30 mm

FXXX	12	XX	XX	S	X	A
Insulator Height F137 H=4.0 F122 H=4.3 F138 H=4.5	Insulator Type 12 Double Row	No. of Positions 02~80 Positions	Pin Plating SN Tin G0 Gold Flash G2 Gold25μ" G3 Gold5μ" G4 Gold10μ" G5 Gold15μ" G6 Gold30μ" S0 Gold Flash/Tin Standard: G0	Angle Options S SMT	Insulator C Nylon-6T D LCP	Series No. A OE=5.20 mm

Pitch 2.0mm Female Header,Straight Double Row
02 to 80 Positions





SPECIFICATIONS:
Current Rating : 1.5AMP
Operation Temperature : -40°C to +105°C
Contact Resistance : 20mΩMax
Insulation Resistance : 1000MΩMin
Withstanding Voltage : AC 500V
Insulator Material : Polyester (UL94V-0)
Standard: Nylon-66
Contact Material : Phosphor Bronze
Contact Plating : Au over 50u"Ni




P.C.B LAYOUT

Pitch 2.0mm Female Header,Straight Single Row
02 to 40 Positions



SPECIFICATIONS:
Current Rating : 1.5AMP
Operation Temperature : -40°C to +105°C
Contact Resistance : 20mΩMax
Insulation Resistance : 1000MΩMin
Withstanding Voltage : AC 500V
Insulator Material : Polyester (UL94V-0)
Standard: Nylon-66
Contact Material : Phosphor Bronze
Contact Plating : Au over 50u"Ni



P.C.B LAYOUT

FXXX	12	XX	XX	D	X	X
Insulator Height F137 H=4.0 F122 H=4.3 F138 H=4.5	Insulator Type 12 Double Row	No. of Positions 02~80 Positions	Pin Plating SN Tin G0 Gold Flash G2 Gold25μ" G3 Gold5μ" G4 Gold10μ" G5 Gold15μ" G6 Gold30μ" S0 Gold Flash/Tin Standard: G0	Angle Options D Straight	Insulator B Nylon-66 C Nylon-6T D LCP	Series No. A OC=2.40 mm B OC=2.70 mm

FXXX	11	XX	XX	D	X	X
Insulator Height F137 H=4.0 F122 H=4.3 F138 H=4.5	Insulator Type 11 Single Row	No. of Positions 02~40 Positions	Pin Plating SN Tin G0 Gold Flash G2 Gold25μ" G3 Gold5μ" G4 Gold10μ" G5 Gold15μ" G6 Gold30μ" S0 Gold Flash/Tin Standard: G0	Angle Options D Straight	Insulator B Nylon-66 C Nylon-6T D LCP	Series No. A OC=2.40 mm B OC=2.70 mm