







Pitch 0.8 & 1.0mm Pin Header : P111,P112,P125

Pitch 0.8*1.2mm Pin Header,SMT Single Base
Dual Row 04 to 100 Positions






SPECIFICATIONS:
Current Rating : 0.75AMP
Operation Temperature : -40°C to +105°C
Contact Resistance : 30mΩ Max
Insulation Resistance : 1000MΩ Min
Withstanding Voltage : AC 500V
Insulator Material : High Temperature Thermoplastic (UL94V-0)
Contact Material : Phosphor Bronze
Contact Plating : Au over 50u"Ni




P.C.B LAYOUT

P111	XX	XX	XX	S	C	XXXX
Insulator Height P111 H=1.38	Insulator Type 12 Single Base Double Row 22 Double Base Double Row	No. of Positions 04-100 Positions	Pin Plating SN Tin G0 Gold Flash G2 Gold2 μ" G3 Gold5 μ" G4 Gold10 μ" G5 Gold15 μ" G6 Gold30 μ" S0 Gold Flash/Tin Standard : G0	Angle Options S SMT	Insulator C Nylon-6T	Series No.

Pitch 1.0mm Pin Header, Straight Single Base
& Double Base Single Row & Double Row
04 to 100 Positions






SPECIFICATIONS:
Current Rating : 0.75AMP
Operation Temperature : -40°C to +105°C
Contact Resistance : 30mΩ Max
Insulation Resistance : 1000MΩ Min
Withstanding Voltage : AC 500V
Insulator Material : High Temperature Thermoplastic (UL94V-0)
Contact Material : Phosphor Bronze
Contact Plating : Au over 50u"Ni






P.C.B LAYOUT

PXXX	XX	XX	XX	D	C	XXXX
Insulator Height P112 H=1.0 P125 H=1.5	Insulator Type 11 Single Base Single Row 12 Single Base Double Row 22 Double Base Double Row	No. of Positions 04-100 Positions	Pin Plating SN Tin G0 Gold Flash G2 Gold2 μ" G3 Gold5 μ" G4 Gold10 μ" G5 Gold15 μ" G6 Gold30 μ" S0 Gold Flash/Tin Standard : G0	Angle Options D Straight	Insulator C Nylon-6T	Series No.

Pitch 1.0mm Pin Header,SMT Single Base
Double Row 04 to 100 Positions








SPECIFICATIONS:
Current Rating : 0.75AMP
Operation Temperature : -40°C to +105°C
Contact Resistance : 30mΩ Max
Insulation Resistance : 1000MΩ Min
Withstanding Voltage : AC 500V
Insulator Material : High Temperature Thermoplastic (UL94V-0)
Contact Material : Phosphor Bronze
Contact Plating : Au over 50u"Ni




P.C.B LAYOUT

PXXX	12	XX	XX	S	C	XXXX
Insulator Height P112 H=1.0 P125 H=1.5	Insulator Type 12 Single Base Double Row	No. of Positions 04-100 Positions	Pin Plating SN Tin G0 Gold Flash G2 Gold2 μ" G3 Gold5 μ" G4 Gold10 μ" G5 Gold15 μ" G6 Gold30 μ" S0 Gold Flash/Tin Standard : G0	Angle Options S SMT	Insulator C Nylon-6T	Series No.

Pitch 1.0mm Pin Header,SMT Double Base
Double Row 04 to 100 Positions



SPECIFICATIONS:
Current Rating : 0.75AMP
Operation Temperature : -40°C to +105°C
Contact Resistance : 30mΩ Max
Insulation Resistance : 1000MΩ Min
Withstanding Voltage : AC 500V
Insulator Material : High Temperature Thermoplastic (UL94V-0)
Contact Material : Phosphor Bronze
Contact Plating : Au over 50u"Ni



P.C.B LAYOUT

PXXX	XX	XX	XX	S	C	XXXX
Insulator Height P112 H=1.0 P125 H=1.5	Insulator Type 22 Double Base Double Row	No. of Positions 04-100 Positions	Pin Plating SN Tin G0 Gold Flash G2 Gold2 μ" G3 Gold5 μ" G4 Gold10 μ" G5 Gold15 μ" G6 Gold30 μ" S0 Gold Flash/Tin Standard : G0	Angle Options S SMT	Insulator C Nylon-6T	Series No.