






Pitch 1.27mm Pin Header : P113,P114,P115,P116,P127

Pitch 1.27mm Pin Header, SMT Double Base Double Row 04 to 100 Positions







SPECIFICATIONS:
 Current Rating : 1AMP
 Operation Temperature : -40°C to +105°C
 Contact Resistance : 20mΩMax
 Insulation Resistance : 1000MΩMin
 Withstanding Voltage : AC 500V
 Insulator Material : Polyester (UL94V-0)
 Standard: Nylon-6T
 Contact Material : Brass
 Contact Plating : Au or Sn over 50u"Ni




P.C.B LAYOUT

PXXX	22	XX	XX	S	C	XXXX
Insulator Height P113 H=1.0 P116 H=1.5	Insulator Type 22 Double Base Double Row	No. of Positions 02-100 Positions	Pin Plating SN Tin G0 Gold Flash G2 Gold2 μ" G3 Gold5 μ" G4 Gold10 μ" G5 Gold15 μ" G6 Gold30 μ" S0 Gold Flash/Tin Standard : G0	Angle Options S SMT	Insulator C Nylon-6T	Series No.

Pitch 1.27mm Pin Header, Straight & Right Angle Single Base Double Row 04 to 100 Positions







SPECIFICATIONS:
 Current Rating : 1AMP
 Operation Temperature : -40°C to +105°C
 Contact Resistance : 20mΩMax
 Insulation Resistance : 1000MΩMin
 Withstanding Voltage : AC 500V
 Insulator Material : Polyester (UL94V-0)
 Standard: Nylon-6T
 Contact Material : Brass
 Contact Plating : Au or Sn over 50u"Ni




P.C.B LAYOUT

PXXX	12	XX	XX	X	C	XXXX
Insulator Height P127 H=1.6 P114 H=2.0 P115 H=2.5	Insulator Type 12 Single Base Double Row	No. of Positions 02-100 Positions	Pin Plating SN Tin G0 Gold Flash G2 Gold2 μ" G3 Gold5 μ" G4 Gold10 μ" G5 Gold15 μ" G6 Gold30 μ" S0 Gold Flash/Tin Standard : G0	Angle Options D Straight R Right Angle	Insulator C Nylon-6T	Series No.

Pitch 1.27mm Pin Header, Straight & Right Angle Double Base Double Row 04 to 100 Positions







SPECIFICATIONS:
 Current Rating : 1AMP
 Operation Temperature : -40°C to +105°C
 Contact Resistance : 20mΩMax
 Insulation Resistance : 1000MΩMin
 Withstanding Voltage : AC 500V
 Insulator Material : Polyester (UL94V-0)
 Standard: Nylon-6T
 Contact Material : Brass
 Contact Plating : Au or Sn over 50u"Ni




P.C.B LAYOUT

PXXX	22	XX	XX	X	C	XXXX
Insulator Height P127 H=1.6 P114 H=2.0 P115 H=2.5	Insulator Type 22 Double Base Double Row	No. of Positions 02-100 Positions	Pin Plating SN Tin G0 Gold Flash G2 Gold2 μ" G3 Gold5 μ" G4 Gold10 μ" G5 Gold15 μ" G6 Gold30 μ" S0 Gold Flash/Tin Standard : G0	Angle Options D Straight R Right Angle	Insulator C Nylon-6T	Series No.

Pitch 1.27mm Pin Header, SMT Single Base Double Row 04 to 100 Positions



SPECIFICATIONS:
 Current Rating : 1AMP
 Operation Temperature : -40°C to +105°C
 Contact Resistance : 20mΩMax
 Insulation Resistance : 1000MΩMin
 Withstanding Voltage : AC 500V
 Insulator Material : Polyester (UL94V-0)
 Standard: Nylon-6T
 Contact Material : Brass
 Contact Plating : Au or Sn over 50u"Ni



P.C.B LAYOUT

PXXX	12	XX	XX	S	C	XXXX
Insulator Height P127 H=1.6 P114 H=2.0 P115 H=2.5	Insulator Type 12 Single Base Double Row	No. of Positions 02-100 Positions	Pin Plating SN Tin G0 Gold Flash G2 Gold2 μ" G3 Gold5 μ" G4 Gold10 μ" G5 Gold15 μ" G6 Gold30 μ" S0 Gold Flash/Tin Standard : G0	Angle Options S SMT	Insulator C Nylon-6T	Series No.