





Pitch 2.54mm Female Header : F128,F133

Pitch 2.54mm Female Header,SMT Single Row
02 to 40 Positions






SPECIFICATIONS:
Current Rating : 3.0AMP
Operation Temperature : -40°C to +105°C
Contact Resistance : 20mΩMax
Insulation Resistance : 1000MΩMin
Withstanding Voltage : AC 1000V
Insulator Material : Polyester (UL94V-0)
Standard: Nylon-66
Contact Material : Phosphor Bronze
Contact Plating : Au or Sn over 50u"Ni




P.C.B LAYOUT

F128	XX	XX	XX	S	X	A
Insulator Height F128 H=5.0	Insulator Type 11 Single Row	No. of Positions 02 ~40 Positions	Pin Plating SN Tin G0 Gold Flash G2 Gold2u" G3 Gold5u" G4 Gold10u" G5 Gold15u" G6 Gold30u" S0 Gold Flash/Tin Standard : G0	Angle Options S SMT	Insulator B Nylon-66 C Nylon-6T D LCP	Series No. A OE=4.4 mm

Pitch 2.54mm Female Header,SMT Single Row
04 to 80 Positions





SPECIFICATIONS:
Current Rating : 3.0AMP
Operation Temperature : -40°C to +105°C
Contact Resistance : 20mΩMax
Insulation Resistance : 1000MΩMin
Withstanding Voltage : AC 1000V
Insulator Material : Polyester (UL94V-0)
Standard: Nylon-66
Contact Material : Phosphor Bronze
Contact Plating : Au or Sn over 50u"Ni




P.C.B LAYOUT

F128	12	XX	XX	S	X	A
Insulator Height F128 H=5.0	Insulator Type 12 Single Base Double Row	No. of Positions 04 ~80 Positions	Pin Plating SN Tin G0 Gold Flash G2 Gold2u" G3 Gold5u" G4 Gold10u" G5 Gold15u" G6 Gold30u" S0 Gold Flash/Tin Standard : G0	Angle Options S SMT	Insulator B Nylon-66 C Nylon-6T D LCP	Series No. A OE=4.4 mm

Pitch 2.54mm Female Header,Straight Single Row
& Double Row 04 to 80 Positions






SPECIFICATIONS:
Current Rating : 3.0AMP
Operation Temperature : -40°C to +105°C
Contact Resistance : 20mΩMax
Insulation Resistance : 1000MΩMin
Withstanding Voltage : AC 1000V
Insulator Material : Polyester (UL94V-0)
Standard: PBT
Contact Material : Phosphor Bronze
Contact Plating : Au or Sn over 50u"Ni




P.C.B LAYOUT

F133	XX	XX	XX	D	X	A
Insulator Height F133 H=6.5	Insulator Type 11 Single Row 12 Double Row	No. of Positions 04 ~80 Positions	Pin Plating SN Tin G0 Gold Flash G2 Gold2u" G3 Gold5u" G4 Gold10u" G5 Gold15u" G6 Gold30u" S0 Gold Flash/Tin Standard : G0	Angle Options D Straight	Insulator A PBT B Nylon-66 C Nylon-6T D LCP	Series No. A OC=3.15 mm

Pitch 2.54mm Female Header,Right Angle Single Row
& Double Row 04 to 80 Positions



SPECIFICATIONS:
Current Rating : 3.0AMP
Operation Temperature : -40°C to +105°C
Contact Resistance : 20mΩMax
Insulation Resistance : 1000MΩMin
Withstanding Voltage : AC 1000V
Insulator Material : Polyester (UL94V-0)
Standard: PBT
Contact Material : Phosphor Bronze
Contact Plating : Au or Sn over 50u"Ni



P.C.B LAYOUT

F133	XX	XX	XX	R	X	A
Insulator Height F133 H=6.5	Insulator Type 11 Single Row 12 Double Row	No. of Positions 04 ~80 Positions	Pin Plating SN Tin G0 Gold Flash G2 Gold2u" G3 Gold5u" G4 Gold10u" G5 Gold15u" G6 Gold30u" S0 Gold Flash/Tin Standard : G0	Angle Options R Right Angle	Insulator A PBT B Nylon-66 C Nylon-6T D LCP	Series No. A OC=3.20 mm